

**NOVORUST 2020 DTM DIRECT POLYURETHANE TOPCOAT, matt
NOVORUST 2050 DTM DIRECT POLYURETHANE TOPCOAT, semi-matt
NOVORUST 2070 DTM DIRECT POLYURETHANE TOPCOAT, semi-gloss
NOVORUST 2090 DTM DIRECT POLYURETHANE TOPCOAT, gloss**

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND THE COMPANY/UNDERTAKING

1.1. Product identifier

**NOVORUST 2020 DTM DIRECT POLYURETHANE TOPCOAT, matt
NOVORUST 2050 DTM DIRECT POLYURETHANE TOPCOAT, semi-matt
NOVORUST 2070 DTM DIRECT POLYURETHANE TOPCOAT, semi-gloss
NOVORUST 2090 DTM DIRECT POLYURETHANE TOPCOAT, gloss**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Topcoats (component A) for application with the use of a spray gun. For professional use in car refinsh.

1.3. Data of the supplier Safety Data Sheet

NOVOL Sp. z o.o.
Ul. Żabikowska 7/9
PL 62-052 Komorniki

Tel: +48 61 810-98-00
Fax: +48 61 810-98-09
www.novol.pl
novol@novol.pl

Person responsible for the Safety Data Sheet

dokumentacja@novol.pl

1.4. Emergency telephone number

+48 61 810-99-09 (from 7.00 to 15.00)

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

The mixture was classified as dangerous pursuant to current regulations - see Section 15.

Classification 1272/2008/EC:

Skin irritation, hazard category 2 (Skin Irrit. 2).

Causes skin irritation. Flammable liquid, hazard category 3 (Flam. Liq. 3). Flammable liquid and vapour.

2.2. Label elements:

Contains:

Xylene

Pictograms:



Signal word:

Warning

H226

Flammable liquid and vapour.

H315

Causes skin irritation.

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261

Avoid breathing vapours/spray.

P271

Use only outdoors or in a well-ventilated area.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

P312

Call a doctor if you feel unwell.

2.3. Other hazards

No available data.

NOVORUST 2020 DTM DIRECT POLYURETHANE TOPCOAT, matt
NOVORUST 2050 DTM DIRECT POLYURETHANE TOPCOAT, semi-matt
NOVORUST 2070 DTM DIRECT POLYURETHANE TOPCOAT, semi-gloss
NOVORUST 2090 DTM DIRECT POLYURETHANE TOPCOAT, gloss

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Not applicable.

3.2. Mixtures

Product identifier

NOVORUST 2020 DTM DIRECT POLYURETHANE TOPCOAT, matt
NOVORUST 2050 DTM DIRECT POLYURETHANE TOPCOAT, semi-matt
NOVORUST 2070 DTM DIRECT POLYURETHANE TOPCOAT, semi-gloss
NOVORUST 2090 DTM DIRECT POLYURETHANE TOPCOAT, gloss

Substance name	Identification numbers	Classification and marking	Concentration [wt%]
Xylene	EC: 215-535-7 CAS: 1330-20-7 Index no.: 601-022-00-9 Registration no.: 01-2119488216-32-XXXX	Flam. Liq. 3; H226; Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit.2; H315	<15
n-Butyl acetate	EC: 204-658-1 CAS: 123-86-4 Index no.: 607-025-00-1 Registration no.: 01-2119485493-29-XXXX	Flam. Liq. 3; H226; STOT SE 3; H336 EUH066	<12
1-methoxy-2-propanol acetate	EC: 203-603-9 CAS: 108-65-6 Index no.: 607-195-00-7 Registration no.: 01-2119475791-29-XXXX	Flam. Liq. 3; H226;	<5
Ethylbenzene	EC: 202-849-4 CAS: 100-41-4 Index no.: 601-023-00-4 Registration no.: 01-2119489370-35-XXXX	Flam. Liq. 2; H225 Acute Tox. 4; H332 STOT RE 2; H373 (hearing organs) Acute Tox. 1; H304	<2

The full text of the hazard statements (H) is provided in Section 16.

NOVORUST 2020 DTM DIRECT POLYURETHANE TOPCOAT, matt
NOVORUST 2050 DTM DIRECT POLYURETHANE TOPCOAT, semi-matt
NOVORUST 2070 DTM DIRECT POLYURETHANE TOPCOAT, semi-gloss
NOVORUST 2090 DTM DIRECT POLYURETHANE TOPCOAT, gloss

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures:

General information:

See section 11 of the Safety Data Sheet.

Inhalation:

Take the victim outside into fresh air, ensure quiet surrounding; in case of no breath, apply artificial respiration. Call a doctor.

Skin:

Take off contaminated clothing. Rinse contaminated skin with plenty of lukewarm water for about 15 minutes. If irritation persists, consult a doctor.

Eyes:

Rinse immediately with plenty of lukewarm water for about 15 minutes, avoid strong water jet-risk of cornea damage, consult a doctor.

Alimentary tract:

Do not provoke vomiting (choking risk). Rinse mouth with water. If conscious, administer 1-2 glasses of warm water. Call a doctor.

Person giving first aid should wear medical gloves.

4.2. Most important symptoms and effects, both acute and delayed

Vapours may cause drowsiness and dizziness. Repeated exposure may cause skin dryness or cracking.

4.3. Indications of any immediate medical attention and special treatment needed

Special measures allowing for specialist and immediate aid should be available in the place of work.

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Powder, foam resistant to alcohols, carbon dioxide, water mist.

5.2. Special hazards arising from the substance or mixture

Fire may cause generation of carbon dioxide and other toxic gases.

5.3. Advice for firefighters

Fire-fighting teams should wear self-contained breathing apparatus and light protective clothing. Cool adjacent tanks by spraying water at a safe distance.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

For persons not being the members of aid giving staff:

Eliminate sources of ignition. Ensure sufficient ventilation of the room. Avoid direct contact with the released substance. Avoid contact with skin and eyes. Personal protection measures - section 8 of the Safety Data Sheet.

For persons giving aid:

Persons giving aid should wear protective clothing made of coated, impregnated fabric, protective gloves (viton), tight protective glasses and breathing apparatus: gas mask with A type absorber.

6.2. Environmental precautions

Prevent leakage to the sewage system, surface waters, underground waters and soil.

6.3. Methods and materials for containment and cleaning up

Stop the leakage (close the liquid inflow, seal), place damaged container in an emergency container, remove the liquid mechanically and place it in an emergency container. In case of large leakage, embank the area. In case of small amounts, collect with the use of a binding agent (e.g. mica, diatomaceous earth, sand).

6.4. Reference to other sections

Personal protection measures - see section 8 of the Safety Data Sheet.

Disposal considerations - see section 13 of the Safety Data Sheet.

NOVORUST 2020 DTM DIRECT POLYURETHANE TOPCOAT, matt
NOVORUST 2050 DTM DIRECT POLYURETHANE TOPCOAT, semi-matt
NOVORUST 2070 DTM DIRECT POLYURETHANE TOPCOAT, semi-gloss
NOVORUST 2090 DTM DIRECT POLYURETHANE TOPCOAT, gloss

SECTION 7: HANDLING AND STORAGE OF THE SUBSTANCES AND MIXTURES

7.1. Precautions for safe handling

Keep away from heat and fire sources. Prevent leakage to the sewage system, surface waters, underground waters and soil. Use in well ventilated rooms. Do not smoke. Do not inhale fumes. Avoid contact with skin and eyes. Take precaution measures against electrostatic discharge. Use personal protection measures - section 8 of the Safety Data Sheet.

7.2. Conditions for safe storage, including any incompatibilities

Store in tightly sealed, original containers. Do not store near large amounts of organic peroxides and other strong oxidants. Take precaution measures against electrostatic discharge. Store in well ventilated rooms at +5 °C to +35°C. Protect from influence of sunrays and heat sources.

7.3. Special end use(s)

Topcoats (component A) for application with a spray gun. For professional use in car refinish taking into consideration the information included in subsections 7.1 and 7.2.

SECTION 8: EXPOSURE CONTROL/PERSONAL PROTECTION

8.1. Control parameters

Xylene CAS 1330-20-7 according to:

- *TRGS 900:* MAK: 100ppm, MAK: 440 mg/m³, 2(II),DFG, H
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 50 mg/m³, 220mg/m³, STEL 100ppm, 441 mg/m³, Sk, BMGV

2-methoxy-1-methylethyl acetate CAS 108-65-6 according to:

- *TRGS 900:* MAK: 50ppm, MAK: 270 mg/m³, 1(I),DFG, EU, Y
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 50 ppm, 274 mg/m³, STEL 100ppm, 548 mg/m³, Sk

Butyl acetate CAS 123-86-4 according to:

- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 150 ppm, 724 mg/m³, STEL 200ppm, 966 mg/m³

Ethylbenzen CAS 100-41-4 according to:

- *TRGS 900:* MAK: 100ppm, MAK: 440 mg/m³, 2(I),EU, H
- Adopted National Exposure Standards for Atmospheric Contaminants in the Occupational Environment [NOHSC:1003(1995)]: TWA 100 ppm, 441mg/m³, STEL 125ppm, 552 mg/m³, Sk

8.2. Exposure control

Respiratory tract protection:

Gas mask with A type absorber (EN 141).

Hand protection:

Protective gloves PN-EN 374-3 (viton, 0.7 mm thick, penetration time > 480 min, nitrile rubber, 0,4 mm thick, penetration time > 30 min)

Eye protection:

Tight protective glasses.

Skin protection:

Proper protective clothing (coated impregnated fabrics).

Workplace:

Fixed fume extraction and general ventilation.

Environmental exposure control:

Prevent leakage to the sewage system, surface waters, underground waters and soil.

NOVORUST 2020 DTM DIRECT POLYURETHANE TOPCOAT, matt
NOVORUST 2050 DTM DIRECT POLYURETHANE TOPCOAT, semi-matt
NOVORUST 2070 DTM DIRECT POLYURETHANE TOPCOAT, semi-gloss
NOVORUST 2090 DTM DIRECT POLYURETHANE TOPCOAT, gloss

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	in accordance with colour template
Odour	strong, powerful
Odour threshold	0.9-9 mg/m ³ (xylene)
pH	not applicable
Melting/freezing point	not applicable
Boiling point	Approx. 120-140°C
Flash point	24°C
Autoignition point	Approx. 415°C
Breakdown point	not specified
Evaporation rate	not specified
Flammability (solid, gas)	not applicable
Explosion limits	% bottom: 1.0 vol% top: 8.0 vol% (xylene)
Vapour pressure	9.0 hPa (20°C)
Vapour density (with regard to air)	4.0 (Butyl acetate)
Density	About 1.3 ÷ 1.5 g/cm ³ (20°C)
Solubility (in water)	poor
N-octanol/water division ratio	1.85 (Butyl acetate)
Viscosity	Approx.. 4000mPas
Explosive properties	not applicable
Oxidizing properties	not applicable

9.2 Other informations

No available data.

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

The product is not reactive under normal conditions.

10.2. Chemical stability

The product remains stable under normal conditions.

10.3. Possibility of hazardous reactions

Carbon monoxide and other toxic gases are generated as a result of thermal decomposition.

10.4. Conditions to be avoided

Flammable liquid and vapour. Avoid contact with strongly oxidizing agents, peroxides, strong acids and bases. Avoid generation and accumulation of static electricity. Protect from the influence of sunrays and heat sources.

10.5. Incompatible materials

Avoid contact with large amounts of organic peroxides, strong acids and bases as well as other strong oxidants.

10.6. Hazardous decomposition products

Carbon monoxide and other toxic gases are generated as a result of thermal decomposition.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

No experimental data available on the preparation. Evaluation was performed based on the data on dangerous ingredients included in the preparation.

a) Acute toxicity

Xylene	LD ₅₀ (rat, ingestion)	5000 mg/kg
	LC ₅₀ (rat, inhalation)	4550 ppm/4h
Butyl acetate	LD ₅₀ (rat, ingestion)	14000 mg/kg
	LC ₅₀ (rat, inhalation)	9660 mg/m ³ /8h
1-methoxy-2-propanol acetate	LD ₅₀ (rat, ingestion)	8532 mg/kg

NOVORUST 2020 DTM DIRECT POLYURETHANE TOPCOAT, matt
NOVORUST 2050 DTM DIRECT POLYURETHANE TOPCOAT, semi-matt
NOVORUST 2070 DTM DIRECT POLYURETHANE TOPCOAT, semi-gloss
NOVORUST 2090 DTM DIRECT POLYURETHANE TOPCOAT, gloss

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

a) Acute toxicity

Ethylbenzene LD₅₀ (rat, ingestion) 3500mg/kg

b) skin corrosion/irritation

Causes skin irritation.

c) serious eye damage/irritation

No available data confirming the hazard class.

d) respiratory or skin sensitisation

The mixture has not been classified as allergenic. No available data confirming the hazard class.

e) germ cell mutagenicity

The mixture has not been classified as mutagenic. No available data confirming the hazard class.

f) carcinogenicity

The mixture has not been classified as cancerogenic. No available data confirming the hazard class.

g) reproductive toxicity

The mixture has not been classified as having any harmful effect on reproduction. No available data confirming the hazard class.

h) STOT-single exposure

No available data confirming the hazard class.

i) STOT- repeated exposure

No available data confirming the hazard class.

j) aspiration hazard

No available data confirming the hazard class.

Exposure methods:

Inhalation: May cause irritation.

Skin: Causes skin irritation

Eyes: May cause irritation.

If swallowed, the substance may cause irritation of the alimentary tract, nausea, vomiting and diarrhoea.

Poisoning symptoms:

Headache and vertigo, fatigue, decreased muscle power, drowsiness and, in exceptional instances, loss of consciousness.

Fumes might cause drowsiness and vertigo. Repeated exposure might cause skin dryness or rupture.

SECTION 12: ECOLOGICAL INFORMATION

No experimental data available on the preparation. Evaluation was performed based on the data on dangerous ingredients included in the preparation.

12.1. Toxicity

1-methoxy-2-propanol acetate

Daphnia magna EC50 (48hours.) > 500 mg/l

Oncorhynchus mykiss (rainbow trout)/LC50 (96 hours) 100-180 mg/l

Number in the catalogue of water hazardous substances: 5033

Water hazard class: 1

Xylene

Daphnia magna EC50 (48hours.) > 7.4 mg/l

Evaluation indicator of acute toxicity for mammals: 3; for fish: 4.1

Number in the catalogue of water hazardous substances: 206

Water hazard class: 2

Butyl acetate

Number in the catalogue of water hazardous substances: 42

Water hazard class: 1

NOVORUST 2020 DTM DIRECT POLYURETHANE TOPCOAT, matt
NOVORUST 2050 DTM DIRECT POLYURETHANE TOPCOAT, semi-matt
NOVORUST 2070 DTM DIRECT POLYURETHANE TOPCOAT, semi-gloss
NOVORUST 2090 DTM DIRECT POLYURETHANE TOPCOAT, gloss

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ethylbenzene Daphnia magna/EC50 (24) 73 mg/l
Number in the catalogue of water hazardous substances: 99
Water hazard class: 1

12.2. Persistence and degradability

No available data.

12.3. Bioaccumulative potential

No available data.

12.4. Mobility in soil

Product very poorly soluble in water.

12.5. Results of PBT and vPvB assessment

No available data.

12.6. Other adverse effects

No available data.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

The product must be disposed of in compliance with proper local and statutory regulations with regard to waste - see point 15. The product should be disposed with entities which are authorised to conduct activity in the area of collecting, recycling or utilization of waste.

Product remains:

Do not dispose the product into the sewage system. Do not store with communal waste. Remove the remains of the mixture carefully and harden with the use of the proper B component, (waste) hardener included in the set. The hardened product is not harmful waste.

CAUTION: harden the remains in small portions and keep them away from flammable products. High amounts of heat are released during chemical reaction!

Contaminated container:

A container containing unhardened remains of the product is harmful waste. Do not store with communal waste. The contaminated container should be disposed with entities which are authorized to collection, recover or disposal.

SECTION 14: TRANSPORT INFORMATION

	ADR/RID	IMO/IMGD	IATA-DGR
14.1. UN number	1866	1866	1866
14.2. UN proper shipping name		RESIN SOLUTION, flammable	
14.3. Transport hazard class(es)	3	3	3
14.4. Packaging group	III	III	III
14.5. Environmental hazards	none	none	none
14.6. Special precautions for user			
Do not transport together with materials of class 1 (excluding materials of class 1.4S) and some materials of classes 4.1 and 5.2. During transport, avoid direct contact with materials of classes 5.1 and 5.2. Do not use an open flame and do not smoke.			
14.7. Transport in bulk according to Annex II of MARPOL Convention and the IBC Code			
Not applicable.			

NOVORUST 2020 DTM DIRECT POLYURETHANE TOPCOAT, matt
NOVORUST 2050 DTM DIRECT POLYURETHANE TOPCOAT, semi-matt
NOVORUST 2070 DTM DIRECT POLYURETHANE TOPCOAT, semi-gloss
NOVORUST 2090 DTM DIRECT POLYURETHANE TOPCOAT, gloss

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Regulation 2006/1907/WE
CLP - Regulation 1272/2008/WE

15.2. Chemical safety assessment

Not performed

SECTION 16: OTHER INFORMATION

Relevant hazard statements listed in Sections 2 to 15:

Flam. Liq.2/3 Flammable liquid. Category 2/3
H226 Flammable liquid and vapour
H225 Highly flammable liquid and vapour
Asp. Tox. 1 Aspiration hazard
H304 May be fatal if swallowed and enters airways
STOT SE 3 Specific target organ toxicity – single exposure, Category 3
H336 May cause drowsiness or dizziness
H335 May cause respiratory irritation
Acute Tox. 4 Acute toxicity. Category 4
H332 Harmful if inhaled
H312 Harmful in contact with skin
STOT RE 2 Specific target organ toxicity – repeated exposure, Category 2
H373 May cause damage to organs through prolonged or repeated exposure
Skin Irrit. 2 Corrosive/irritating effect on skin. Category 2
H315 Causes skin irritation, Category 2
EUH066 Repeated exposure may cause skin dryness or cracking
Eye Irrit.2 Serious eye damage/eye irritation. Category 2
H319 Causes serious eye irritation

Abbreviations and acronyms:

CAS no. – a numerical symbol ascribed to a chemical substance by the American organization, Chemical Abstracts Service (CAS).

EC no. – a number ascribed to a chemical substance in the **E**uropean **L**ist of **N**otified **C**hemical **S**ubstances (ELINCS), or a number in the "No-longer polymers" publication listed **E**uropean **I**nventory of **E**xisting **C**hemical **S**ubstances (EINECS).

MPC – (Poland: NDS) maximum permissible concentration of health hazardous substances in the work place.

MPIC – (Poland: NDSch) maximum permissible instantaneous concentration.

MPCC – (Poland: NDSP) maximum permissible ceiling concentration.

PCB – (Poland: DSB) permissible concentration in biological material.

UN number – four-digit identification number of a substance, preparation or product pursuant to UN model regulations.

ADR – European agreement on international road transport of hazardous materials.

IMO – International Marine Organization.

RID – Regulations for international rail transport of hazardous materials.

IMDG-Code – International Marine Code for Dangerous Materials.

ICAO /IATA – Technical Instructions for the Safe Transport of Dangerous Goods by Air.

The information is based on our current knowledge. This document shall not constitute warranty for product characteristics. Classification was made by calculation method according to the classification rules contained in Regulation 1272/2008/WE.

Other sources of information

ECHA European Chemicals Agency

TOXNET Toxicology Data Network

IUCLID International Uniform Chemical Information Database

Changes: General update

Trainings:

In handling, health and safety while working with hazardous substances and mixtures.

In transport of hazardous goods pursuant to the requirements of ADR regulations.

Issued by: NOVOL Sp. z o.o.